


## TPTCM112III

### 112mm ticket / receipt printer

- Best printing quality (200 DPI)
- Paper width: 112mm
- Paper thickness: from 63 to 100  $\mu$ m
- Printing > 140 mm/sec
- Up to 160mm paper roll diameter
- RS232 + USB interfaces
- Highly reliable cutter: > 1,000,000 cuts
- Sensors: ticket presence, near paper end, black mark and label gap (optional)



## CHARACTERISTICS

- 1D/ 2D (QR CODE) barcode printing feature
- International fonts on-board: any language available
- Label gap and black mark sensors (optional)
- Strong motorised dispenser available
- Versatile: **optional** paper roll holder - 5 positions
- Illuminated paper outfeed (LED)
- Plastic paper bezel (optional)
- Sturdy and reliable: robust and light mechanical parts
- DIN power supply connector
- Cut&drop version available
- Plastic paper bezel (optional)

## APPLICATIONS:

- Self-service kiosks
- Information kiosks
- Form and document kiosks
- Banking machines and cash dispensers

## SOFTWARE:




**PrinterSet SOFTWARE :** to update logos, edit characters, set operating parameters and update the printer firmware. It allows you to create a file including the different SW customizations and send them to the printer via the interface provided, for easy and fast setting.

- Auto-installing drivers for WinXP/Vista/7/8
- Linux Driver, 32/64 bit compatible
- Remote Status Monitor
- CustomPowerTool


## TECHNICAL SHEET

<b>Printing Method</b>	Thermal with fixed head
Number of dots	8 dots/mm
Resolution	203 DPI
Printing (mm/sec)	>140 mm/sec
Character set	International (default), Chinese, Korean
Supported Barcode	UPCA, UPCE, EAN13, EAN8, CODE39, ITF, CODABAR, CODE93, CODE128, CODE32, PDF417, DATAMATRIX, AZTEC, QR CODE
Printing Format	Height and width from 1 to 8, bold, negative, underlined, script
Printing Direction	Straight, 90°, 180°, 270°
Paper width	112 mm
Paper weight	from 60 to 90 g/m <sup>2</sup>
Paper thickness	from 63 to 100 $\mu$ m
Roll Dimension	Max 160mm (120mm without roll holder)
Emulation	CUSTOM/POS, TPTCMII
Interfaces	RS232 + USB
Data Buffer	16 KB
Flash Memory	1MB internal, 4MB external
RAM Memory	128Kb internal, 8MB external
Drivers	WIN XP, Vista-7-8 (32/64bit), Linux
Software Tools	PrinterSet, CustomPowerTool, Status Monitor
Power supply	24 Vdc $\pm$ 10%
Medium consumption	1.7A (12.5% dots turned on)
MTBF	122,000 hours (electronic board )
Head Life	100 Km / 100M pulses
MCBF	1,000,000 cuts
Operating temperature	0°C + 50°C
Dimensions	227.4(L)x95.3(H)x171.5(W) mm with short paper mouth 300(L)x95.3(H)x171.5(W) mm with dispenser
Weight	1.7 Kg (without ejector)2.1 Kg (with ejector)


## MODELS




**915KV010200300**  
 PRINTER TPTCM112III CUTTER  
 AND NOTCH



**915KV010400300**  
 PRINTER TPTCM112III LABEL  
 AND CUTTER



**915KV010300300**  
 PRINTER TPTCM112III STRONG  
 CUTTER



**915KV010100300**  
 PRINTER TPTCM112III USB RS232  
 EJECTOR

---

CUSTOM SPA - Via Berettine, 2 - 43010 Fontevivo PR - VAT: IT02498250345 - TEL: +39 0521 680111 - FAX: +39 0521 610701 - UNIQUE CODE: T180W10

The technical data on this website are not binding and may be changed without advanced notice.

Last update: 03 March 2020