

TM-T70II POS Receipt Printer

Contact Us
562-276-1314



The reliable, high-performance front-loading thermal receipt printer.

Epson's mPOS-friendly TM-T70II POS printer, with its small size and low height (only 4.49" high), is designed to fit under a counter, in kiosks and other small spaces. It features fast printing of up to 250mm/second, industry-leading reliability, dual interfaces and more. And it supports all the leading mobile operating systems including iOS, Android and Windows.

Model: C31CD38124

Overview

- **Versatile** — supports 3" media width
- **Fast** — prints up to 250 mm/sec
- **Highly configurable with Connect-It™ modules** — plus wireless and Bluetooth® capabilities
- **Compatible** — works with both traditional and mobile (iOS®, Android™ and Windows®) POS systems; includes ESC/POS® OPOS and Java POS drivers
- **ePOS™ print technology** — for easy setup with iOS, Android and Windows mobile devices and Windows drivers for desktop PCs
- **Wireless setup** — with SimpleAP (wireless SKU only)

- **Dual interface** — options include USB, Ethernet, wireless and Bluetooth
- **Energy efficient** — low power consumption; ENERGY STAR® qualified¹
- **Comprehensive service and support** — dedicated technical resource team, customized solutions, 2-year limited warranty

What's In The Box:

- TM-T70II Thermal Printer
- Thermal roll paper (starter roll for operation check)
- Bracket for holding USB cable
- AC adapter/AC cord
- Set-up guide
- CD ROM (includes User Manual)
- Technical Manual, drivers

Specifications

Print Other:

Printing Technology:

Thermal line printing

Print Speed:

Max. 250mm/sec (9.84"/sec)

General:

Dimensions:

4.92" x 7.64" x 4.49" (125 x 194 x 114 mm) (W x D x H)

Weight:

3.75 lbs (1.7 kg)

Safety Approvals:

- Safety standards: UL/CSA/EN/TUV/GOST-R
- EU directive: RoHS and WEEE compliant

Case Color:

Epson Dark Gray

Print Fonts:

Print Fonts:

Font A: 12 x 24 dots; Font B: 9 x 17 dots (W x H)

Column Capacity:

(A, B) 80mm: 42/56

Character Size:

- (Std / Double H, Double W / Double W and Double H)
- Font A: 1.41 x 3.39 / 1.41 x 6.77 / 2.82 x 3.39 / 2.82 x 6.77mm
- Font B: 0.99 x 2.40 / 0.99 x 4.80 / 1.98 x 2.40 / 1.98 x 4.80mm

Fonts:

Font A: 12 x 24 dots; Font B: 9 x 17 dots (W x H)

Character Set:

- 95 Alphanumeric, 18 set International, 128 x 43 Pages
- Two dimensional code: PDF417, QRCode, MaxiCode, 2D GS1 DataBar, Composite Symbology

Characters per Inch:

20.0 and 15.0 cpi

Barcode:

UPC-A, UPC-E, JAN13 (EAN13), JAN8 (EAN), CODE39, ITF, CODABAR (NW-7), CODE93, CODE128, GS1-128, GS1 DataBar.

Media Handling:

Media Dimensions:

80mm: 3.13" ± 0.02" x 3.27" diameter (79.5 ± 0.5(W) x 83mm)

Connectivity:

Standard Connectivity:

Built-in USB interface + another selection: serial, parallel, powered USB, Ethernet, 802.11b/g/n (2.4GHz) and 802.11a/n (5GHz) or Bluetooth 2.1 + EDR

Printing from a Mobile Device:

- Wi-Fi (802.11): iOS, Android™ and Windows®
- Bluetooth: iOS, Android™ and Windows®

POS Details:

Reliability:

- MTBF: 360,000 hours
- MCBF: 65,000,000 lines
- Auto Cutter: 1.7 million cuts

D.K.D.:

2 drivers

Software Included:

Drivers & tool software (APD, OPOS™, JavaPOS™, OPOS NET™, TM Virtual port driver, Linux® Cups driver, Mac OS® X driver, TM-T70II Utility, EpsonNet Simple Viewer)

Options:

External buzzer unit, cable management cover, shelf bracket

Power:

Power Consumption:

Approx. 2.0A (mean)

Power Source:

100 – 240V AC, 50/60 Hz; External (AC cable included)

© 2022 Epson America, Inc.