

## TG2480HIII


### 80mm ticket / receipt printer

- Metal frame (galvanized/aluminium alloy)
- High print quality (200 DPI)
- Paper width: 80mm
- Paper thickness: from 63 to 85 µm
- Printing > 150 mm/sec
- RS232 and USB interfaces
- Barcodes: UPC-A, UPC-E, EAN13, EAN8, CODE39, ITF, CODABAR, CODE93, CODE128, CODE32, QR CODE
- Characters: European, International, Portuguese, Nordic, Arabic, Chinese and Russian
- Highly reliable cutter: over 1,000,000 cuts
- Sensors: head temperature, paper presence, anti paper jamming, ticket collection, paper end and near paper end



## CHARACTERISTICS

- Patented Anti Jamming System
- Multi-position paper roll
- Metal structure that provides increased rigidity for the printing mechanism and facilitates motor heat dissipation, resulting in improved stability and reliability over time
- Improved distribution of the head-roller pressure, resulting in improved printing quality



Exclusive patented anti-jamming system. The design includes an integral chute that protrudes from the front of your panel, making mounting and integration simple.

## APPLICATIONS:

- Self-service kiosks
- Banking machines
- Gaming machines
- Parking meters
- Photo kiosks
- Queue management systems
- Vending machines


## SOFTWARE:

- Auto-installing drivers for Win XP/ Vista/ 7 (+64 bit support)
- Windows CE 3.0/5.0 Drivers (PLC )
- OPOS Drivers
- Linux driver
- Remote monitor status
- PrinterSet
- CustomPowerTool

## TECHNICAL SHEET

<b>Printing Method</b>	Thermal with fixed head
Number of dots	8 dots/mm
Columns	43 - 60 - 76
Resolution	203 DPI
Printing (mm/sec)	150mm/sec
Character set	PC437, PC850, PC860, PC863, PC865, PC858, PC866, GB2312
Printing Format	Normal, height and width from 1 to 4, bold, negative, underlined, script
Printing Direction	Straight, 180°
Paper width	80 mm
Paper weight	from 55 to 80 g/m <sup>2</sup>
Paper thickness	from 63 to 85 $\mu$ m
Roll Dimension	max 90mm
Sensors	Head temperature, paper presence, paper jamming, ticket collection, optional near paper end sensor
Emulation	Custom/POS, TGH
Interfaces	RS232 + USB
Data Buffer	2 kB
Flash Memory	1 MB
Graphic Memory	2 608x430 dot logos
Drivers	XP / Vista / 7 / OPOS / Windows CE 3.0/5.0 / Linux
Software Tools	Status Monitor, PrinterSet, CustomPowerTool
Power supply	24V +/- 10%
Medium consumption	0.8A (12.5% dots turned on)
MTBF	450,000 hours (electronic board)
Head Life	50Km/100M pulses
Operating temperature	0°C + 50°C
Dimensions	271,5(L)x102(H)x130,2(W) mm (without ejector) 260,2(L)x102(H)x130,2(W) mm (with ejector)
Weight	1130 g (without ejector) 1250 g (with ejector)

## MODELS



**915CH020100300**  
PRINTER TG2480HIII USB RS232

---

CUSTOM SPA - Via Berettine, 2 - 43010 Fontevivo PR - VAT: IT02498250345 - TEL: +39 0521 680111 - FAX: +39 0521 610701 - UNIQUE CODE: T180W10

The technical data on this website are not binding and may be changed without advanced notice.

Last update: 03 March 2020