

# RJ-4230B/RJ-4250WB

## 4" Mobile Printing Solution



### Top Features:

#### Compatible with Windows®

- Print from Windows PC's through the USB interface, Bluetooth or Wi-Fi^

#### Ready to Integrate with iOS® & Android apps

- Using Brother SDK (3<sup>rd</sup> party development required)
- Brother Print service plug-in (Download from Google play store)
- Mobile Deploy App for remote configuration (Download from Google play store or iOS app store)

#### Portable Robust Design

- Designed to withstand even the harshest conditions. 2.1m drop tested, IP54 rating out of the box.

#### Fast Print Speed

- Maximum 5ips (127mm/sec)
- Maximum print length up to 3000mm

#### LCD Display

- Mono Backlit LCD display
- Intuitive, easy to use

#### Connectivity

- Bluetooth V4.2 supporting Low Energy mode and extended connectivity range (MFi certified)
- Wireless LAN 802.11 a/b/g/n supporting 2.4GHz and 5GHz bands^

### General

<b>Carton contents</b>	Belt Clip Adjuster guide locks Documentation
<b>Language support</b>	Dansk, Deutsch, English, Español, Français, Italian, Nederlands, Norsk, Português, Suomi, Svenska

### Dimensions & Weights

<b>Without carton</b>	153(w) x 159(d) x 68(h)   850g
-----------------------	--------------------------------

### Built In Features

<b>Printing Method</b>	Direct Thermal
<b>Printing speed</b>	Maximum 5ips (127mm/sec) (*Under Brother standard environment)
<b>Maximum print width</b>	104mm
<b>Maximum print length</b>	3000mm
<b>Print resolution</b>	203dpi
<b>Number of labels per battery charge</b>	Li-ion battery: approx. 10,000 labels (continuous print, <b>(*Under Brother standard environment)</b> )

<b>Interfaces</b>	USB Ver.2.0 (Full Speed) (mini-B). Bluetooth Version.4.2 supporting Low Energy NFC (Passive) Wireless LAN 802.11a/b/g/n supporting 2.4GHz and 5GHz^ (supporting Airprint® from iOS® devices)
-------------------	---

<b>Mobile OS support</b>	Android 4.0.3 or later iOS® 7 or later (requires 3 <sup>rd</sup> party app development using Brother SDK), further information available at <a href="http://www.brother.eu/developer">www.brother.eu/developer</a>
--------------------------	---

<b>Printer commands</b>	Raster ESC/P P-touch Template ZPL emulation CPCL emulation
-------------------------	--

<b>Printer driver</b>	Microsoft® Windows® 7 / Windows® 8 / Windows® 8.1 / Windows® 10  Microsoft® Windows® Server 2008 / Server 2008R2 / Server 2012 / Server 2012R2 / Server 2016^
-----------------------	--

<b>Software</b>	<b>P-touch Editor</b> – Barcode label design software <b>Brother Print Service Plugin</b> – Driverless printing from Android devices (version 5.0 and above) <b>Mobile Deploy App</b> – remote printer configuration <b>Brother Font Manager</b> – font download tool (Windows® only via USB) <b>Printer Settings Tool</b> – device configuration software (Windows® only via USB)
-----------------	--

<b>Internal fonts &amp; sizes</b>	<ESC/P> Bitmap font: Gothic, Letter Gothic Bold, Helsinki Font sizes <16, 24, 32dot> Outline font: Gothic, Letter Gothic Bold, Helsinki, Brussels Font size 400dot (max) <P-touch Template> Outline font: Gothic, Letter Gothic Bold, Helsinki Font size 400dot (max)  Downloadable font support** via Font Manager software
-----------------------------------	---

### Environmental

<b>Drop Protection</b>	2.1m (Under Brother standard environment)
<b>Operating Temperature</b>	Battery -20°C to 55°C AC adapter -10°C to 40°C Car adapter -10°C to 50°C
<b>Operating Humidity</b>	10% to 90% non-condensing
<b>Charging Temperature</b>	0°C to 40°C
<b>Storage Temperature</b>	-20°C to 60°C
<b>Storage Humidity</b>	10% to 90% non-condensing

### Supplies

<b>RD roll type</b>	RD-M01E5(Receipt – 101.6mm x 27.7m ) RD-M03E1 (72 Labels – 101.6mm x 152.4mm) RD-R03E5(Receipt – 58mm x 12m )
---------------------	---

### Optional Accessories

<b>Battery</b>	Rechargeable Li-ion Smart battery (PA-BT-006):7.2V continuously printing 10,000 labels <b>(*Under Brother standard environment)</b>
<b>Shoulder Strap</b>	PA-SS-4000
<b>Power Options</b>	PA-CR-002 Single Cradle/Charger PA-BC-003 Single Battery Charger PA-AD-600 AC Adapter PA-CD-600CG Cigar lighter plug PA-CD-600WR Permanently wired

\*Connected by USB with new battery and full charge. Printed by Brother specified data (7% coverage 102mm x 29mm) at 23° C.

\*\*Font Licensee permissions are required.

^ RJ-4250WB model only