

# **SCANMATIC**

# **2D BARCODE SCANNER**

SCANMATIC SM420 is the professional barcode scanners designed to offer the best of the experience to user, in terms of speed, simplicity of use and mistakes absence.

SCANMATIC readers have a modern design with a rugged housing, IP42 protection and they guarantee unique performances. Thanks to the optional stand it is possible to use the reader hands-free. In addition to sustain the scanner, the stand permits to activate "intelligent activation" function thanks to which it is possible the barcodes automatic scan, when presented in front of the reader.

SCANMATIC guarantees an exceptional operation speed not having to orient the code for reading.





**FEATURES** SM420

#### **GENERAL**

**INTERFACES USB** 

SUPPORTED BARCODES 1D: UPC-A, UPC-E, EAN-8 / JAN-8, EAN-13 / JAN-13, Code 39, Code 128, Interleaved 25, Industrial 25, Ma-

trix 25, Codabar / NW7, Code 93, China Posta, MSI / Plessey, Telepen, GS1 Databar Omni-direzionale, GS1

Databar Limited, GS1 Databar Expended

Opzione: Aztec, Micro PDF 417, Micro QR Code, Han Xin Code, GM Code

2D: Data Matrix, PDF 417, QR Code

Opzione: Aztec, Micro PDF 417, Micro QR Code, Han Xin Code, GM Code

### OPTICAL

OPTICAL SENSOR	CMOS SENSOR
LIGHT	LED white light
RESOLUTION	3 mil/0.076 mm@PCS90% Code39, 8 mil/0.2 mm@PCS90% QRCode
SEALING	IP42 water and dust resistance
SCAN SPEED	60 fps (at full resolution)
PRINT CONTRAST	PCS30%@5 mil/0.127 mm
READING DISTANCE	250 mm@20 mil/0.5mm, PCS90%
INDICATOR	Beep and LED

#### **OTHER DATA**

POWER CONSUMPTION	370 mA
POWER SUPPLY	+5 V USB (±9 V RS232 optional)
OPERATING TEMPERATURE	0°C to 50°C (32 °F to 122 °F)
DROP RESISTANCE	180 cm
MATERIALS	ABS/Rubber
DIMENSIONS	73.50 mm (W) × 173 mm (L) × 76.2 mm (H)
MTBF	50.000 hours

## **Custom ScannerSet:**

configuration software for SCANMATIC range scanners. Easily configure your barcode reader with an intuitive user interface. Connect the device to the PC via USB and launch the app.



